




项目/参数/认证				
额定电压(Rated Voltage) [V]	250	250	250	250
额定电流(Rated Current) [A]	16	17.5	17.5	10
额定线经平方(Wire Range) [mm²]	0.2-1.5	0.2-1.5	0.2-1.5	0.2-1.5
额定线经线号(Wire Range) [AWG]	24-16	24-16	24-16	24-16
冲击电压 (Impulse withstand voltage)	4 (KV)			
剥线长度(Stripping Length) [mm]	8-9 (mm)			
绝缘材料(Insulation Material)	PA66 UL94V-0			
导体材料(Contact Material)	黄铜 (brass)			
导体表面镀层(Contactive Coating)	镀锡 (Dumb tin)			
间距(Pitch) [mm]	3.5			
级数(Poles) [P]	2-32P			
工作温度(Operating temperatur) [°C]	-40℃ ~ +105℃			
焊锡温度(Soldering temperature) [°C]	250℃ /5S			



linear dimension (Tolerances Standard GB/T 14486-2008)								—		
variable range		over 6	over 10	over 30	over 60	over 100	over 160		over 10	over 100
	to 6	to 10	to 30	to 60	to 100	to 160	to 10	to 100	to 100	
tolerance	±0.20	±0.30	±0.50	±0.70	±1.00	±1.30	±1.60	0.10	0.30	0.60

单位/UNITS	mm	尺寸/SIZE	A4	比例/SCALE	1:1	第三视角/THIRD ANGLE PROJECTION	版本/REV	VO
东莞市地安电子科技有限公司								
						名称/TITLE	DA803-3.5卡扣	